

...closing the gap



Part Number	Frequency Range	VSWR		Average Power (Watts)	Peak Power (Watts)	Length (inches)	Diameter (inches)
		DC	(Max)				
N-Female Termination: 401-2	DC-6.0 GHz	DC-6.0	1.20:1	2	2000	1.6	0.75
N-Male Termination: 401-1	DC-6.0 GHz	DC-3.0 DC-6.0	1.10:1 1.20:1	2	2000	1.5	0.82
7/16 DIN Male Termination: 401-11	DC-3.0 GHz	DC-1.0 1.0-2.0 2.0-3.0	1.10:1 1.15:1 1.20:1	2	500	2	1.06
SMA-Male Termination: 464-1	DC-18.0 GHz	DC-4.0 4.0-8.0 8.0-12.4 12.4-18.0	1.05:1 1.10:1 1.15:1 1.20:1	2	1000	0.58 ±.05	0.28 & 5/16" Hex
7/16 DIN Male Termination: 405-11	DC-3.0 GHz	DC-1.0 1.0-2.0 2.0-3.0	1.10:1 1.15:1 1.20:1	5	1000	2	0.95
N-Male Termination: 405-1	DC-3.0 GHz	DC-1.0 1.0-3.0	1.10:1 1.15:1	5	2000	1.5	0.82
N-Female Termination: 405-2	DC-3.0 GHz	DC-1.0 1.0-3.0	1.10:1 1.15:1	5	2000	1.6	0.75
SMA-Male Termination: 400-7	DC-12.4 GHz	DC-6.0 6.0-12.4	1.15:1 1.25:1	5	1000	1.12	0.5
SMA-Female Termination: 400-8	DC-12.4 GHz	DC-6.0 6.0-12.4	1.15:1 1.25:1	5	2000	1	0.5
7/16 DIN Termination: 417-11	DC-2.5 GHz	DC-1.0 1.0-2.5	1.10:1 1.15:1	10	500	2.16	1
SMA-Male Termination: 417-1	DC-12.4 GHz	DC-4.0 4.0-12.4	1.10:1 1.25:1	10	2000	1.97	0.645
SMA-Female Termination: 417-2	DC-12.4 GHz	DC-4.0 4.0-12.4	1.10:1 1.25:1	10	2000	1.97	0.645
N-Male Termination: 403-1	DC-12.4 GHz	DC-3.0 3.0-6.0 6.0-12.4	1.15:1 1.20:1 1.50:1	15	2000	2.5	1.25
N-Female Termination: 403-2	DC-12.4 GHz	DC-3.0 3.0-6.0 6.0-12.4	1.15:1 1.20:1 1.50:1	15	2000	2.55	1.25

...closing the gap



Part Number	Frequency Range	VSWR		Average Power (Watts)	Peak Power (Watts)	Length (inches)	Diameter (inches)
		DC	(Max)				
N-Female Termination: 401-2	DC-6.0 GHz	DC-6.0	1.20:1	2	2000	1.6	0.75
N-Male Termination: 401-1	DC-6.0 GHz	DC-3.0 DC-6.0	1.10:1 1.20:1	2	2000	1.5	0.82
7/16 DIN Male Termination: 401-11	DC-3.0 GHz	DC-1.0 1.0-2.0 2.0-3.0	1.10:1 1.15:1 1.20:1	2	500	2	1.06
SMA-Male Termination: 464-1	DC-18.0 GHz	DC-4.0 4.0-8.0 8.0-12.4 12.4-18.0	1.05:1 1.10:1 1.15:1 1.20:1	2	1000	0.58 ±.05	0.28 & 5/16" Hex
7/16 DIN Male Termination: 405-11	DC-3.0 GHz	DC-1.0 1.0-2.0 2.0-3.0	1.10:1 1.15:1 1.20:1	5	1000	2	0.95
N-Male Termination: 405-1	DC-3.0 GHz	DC-1.0 1.0-3.0	1.10:1 1.15:1	5	2000	1.5	0.82
N-Female Termination: 405-2	DC-3.0 GHz	DC-1.0 1.0-3.0	1.10:1 1.15:1	5	2000	1.6	0.75
SMA-Male Termination: 400-7	DC-12.4 GHz	DC-6.0 6.0-12.4	1.15:1 1.25:1	5	1000	1.12	0.5
SMA-Female Termination: 400-8	DC-12.4 GHz	DC-6.0 6.0-12.4	1.15:1 1.25:1	5	2000	1	0.5
7/16 DIN Termination: 417-11	DC-2.5 GHz	DC-1.0 1.0-2.5	1.10:1 1.15:1	10	500	2.16	1
SMA-Male Termination: 417-1	DC-12.4 GHz	DC-4.0 4.0-12.4	1.10:1 1.25:1	10	2000	1.97	0.645
SMA-Female Termination: 417-2	DC-12.4 GHz	DC-4.0 4.0-12.4	1.10:1 1.25:1	10	2000	1.97	0.645
N-Male Termination: 403-1	DC-12.4 GHz	DC-3.0 3.0-6.0 6.0-12.4	1.15:1 1.20:1 1.50:1	15	2000	2.5	1.25
N-Female Termination: 403-2	DC-12.4 GHz	DC-3.0 3.0-6.0 6.0-12.4	1.15:1 1.20:1 1.50:1	15	2000	2.55	1.25

...closing the gap



Part Number	Frequency Range	VSWR (Max)		Average Power (Watts)	Peak Power (Watts)	Length (inches)	Diameter (inches)
		DC-2.0	1.10:1				
N-Male Termination: 404-1	DC-6.0 GHz	DC-2.0	1.10:1	35	5000	2.77	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
N-Female Termination: 404-2	DC-6.0 GHz	DC-2.0	1.10:1	35	5000	2.73	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
SMA-Male Termination: 404-7	DC-6.0 GHz	DC-2.0	1.10:1	35	5000	2.77	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
SMA-Male Termination: 404-7	DC-6.0 GHz	DC-2.0	1.10:1	35	5000	2.77	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
SMA-Male Termination: 404-8	DC-6.0 GHz	DC-2.0	1.10:1	35	5000	2.73	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
N-Male Termination: 480-1	DC-6.0 GHz	DC-2.0	1.10:1	50	5000	4.67	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
N-Female Termination: 480-2	DC-6.0 GHz	DC-2.0	1.10:1	50	5000	4.6	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
SMA-Male Termination: 480-7	DC-6.0 GHz	DC-2.0	1.10:1	50	5000	4.67	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
SMA-Male Termination: 480-8	DC-6.0 GHz	DC-2.0	1.10:1	50	5000	4.6	1.62
		2.0-4.0	1.20:1				
		4.0-6.0	1.30:1				
N-Male Termination: 490-1	DC-4.0 GHz	DC-1.0	1.10:1	100	5000	6.79	2.73
		1.0-2.4	1.20:1				
		2.4-4.0	1.30:1				
N-Female Termination: 490-2	DC-4.0 GHz	DC-1.0	1.10:1	100	5000	6.75	2.73
		1.0-2.4	1.20:1				
		2.4-4.0	1.30:1				
N-Male Termination: CTN-250	DC-3.0 GHz	DC-1.0	1.10:1	250	5000	2.45	W=2.00, H=1.06
		1.0-2.0	1.15:1				
		2.0-3.0	1.30:1				
N-Male Termination: CTN-500	DC-2.4 GHz	DC-1.0	1.15:1	500	5000	8	W=1.50
		1.0-2.4	1.35:1				