



>> IN-BUILDING AMPLIFIER Model 140

Extends Coverage

The Model 140 In-Building Amplifier, featuring 40 dB of gain, is the perfect solution for small office/ home office installations. This easy to install BDA was designed for placement on a desk or counter top but can also be wall mounted if preferred. The Model 140 provides, as standard, the following integrated features:

- The Model 140 continuously monitors its operation for instability and responds by reducing the gain of the amplifier to eliminate an unstable condition.
- Automatic Gain Control (AGC) lowers the amplifier gain in order to reduce strong signals.
- The overload shutdown with automatic recovery feature detects very strong signals that cannot be adequately controlled by the AGC. The amplifier will disable itself and then attempt to recover. The amplifier is active for a very brief period of time (less than 30 milliseconds) until the overload condition is eliminated.
- Higher power output than any other amplifiers in its class with approximately 100 milliwatts (+20 dBm) in the uplink and downlink for all models.

Specifications

Gain	40 dB
Linear Output Power	+19 dBm (typical)
Propagation Delay	<150 nsec.
Noise Figure	4 dB
Dimensions/ Weight	6.24" x 3.05" x 1.13" / 2 lbs
Connectors	N-Female
Power Requirements	+5 Vdc, 1.2A
Indicator LEDs	Power, AGC, Isolation, Shutdown